



Performance. Power.
Productivity.™

D Series


Clinching Stapler

SENCO's extremely lightweight (2.7 lb) D Series Staplers are designed for packaging applications. D Series Staplers provide excellent performance with a minimum of maintenance.



Specifications

Item #	030002N
Mode of Operation	Sequential Actuation
Reg. Operating Pressure	70-90 psi (4.6- 8 bar)
Air Inlet	1/4" NPT
Tool Weight	2.7 lbs (1.2 kg)
Height	7.75" (197 mm)
Length	8" (203 mm)
Lip Length	.5" (13 mm)
Jaw Opening	.56" or .81"
Throat Depth	4.75" (121 mm)
Fastener Capacity	112



Fastener Specifications

Gauge	20
Crown	1/2" (12.7 mm)
Length	5/16" - 1/2" (8mm - 12.7 mm)
Finish	Galv.
Collation	glued strip

Applications

Used wherever two materials must be stapled and clinched. Used in light assembly operations joining to corrugated, light assembly and packaging. In shoemaking, used for attaching wooden or steel shanks, upper to insoles, vamps, straps, ornaments, and buckles. Widely used in corrugated box fabrication

Features and Benefits

- Dependable time-tested design
- Great for hand-held or mounted applications

SENCO® 20 Ga. 1/2" Crown Fine Wire

Bedding, packaging and set-up boxes

Length	Item Code	Carton Count	Point	Finish	Coating
3/16	F05BAAP	24.M	Blunt	Galv	Plain
3/8	F06BAA	10.M	Blunt	Galv	Plain
3/8	F06BAAP	24.M	Blunt	Galv	Plain
1/2	F08BAAN	10.M	Blunt	Galv	Plain
3/8	F06BGA	10.M	Blunt	Stainless	Plain

Contact Actuation Trigger (also known as dual action, bounce or bottom fire) operates in the following sequence- pull the trigger first and keep the trigger pulled while moving the tool along the work surface with a bouncing motion, depressing the safety element at the nose of the tool against the work surface where the fastener is to be driven. This trigger is recommended for use by trained professionals only in high production or volume applications.

Sequential Actuation Trigger (also known as restrictive trigger or trigger fire) operates in the following sequence - depress the safety element at the nose of tool against the work surface then pull the trigger. After each fastener is driven, release the trigger and lift the tool off the work surface before starting the sequence again. This trigger is recommended and acceptable for most applications.

For additional information on how SENCO will save you time, reduce costs, and increase quality, call us at 1-800-543-4596 to find your nearest Authorized Senco Dealer or Distributor or visit our web site at: www.senco.com