



Performance. Power.
Productivity.™

FinishPro® 2n1

18 Ga. Finish Nailer and Stapler

The FinishPro 2N1 is lightweight, flexible and loaded with features. The 2N1 offers both brad nailing and stapling in a single tool for maximum versatility. The FinishPro 2N1 drives 18 gauge brad nails from 5/8" - 1-1/4" and 18 gauge staples from 1/2" - 1".



Applications

Nailing: Furniture repair, cabinets, drawer assembly, case backs, small trim, chair rails, picture frames and ornamentals

Stapling: Shelving, soffits, fascia, cabinets, picture frames and craft assembly

Features and Benefits

- 2 in 1 design allows for stapling and nailing in a single tool
- Adjustable depth-of-drive
- Rear exhaust – keeps oil and dust away from the work surface
- Full soft grip – for comfort and control
- Low load indicator – visible fastener indicator
- No-mar pad – to protect work materials
- One-year warranty
- Includes case, fitting, oil, hex wrench

SENCO® 18 Ga. Straight Strip Brad Nails

Cabinets, decorative trim, picture frames and ornamentals

Length	Item Code	Carton Count	Head	Point	Finish	Coating	Package
5/8"	AY10EAA	5.M	Slight	Chisel	Galv	Plain	Box
3/4"	AY11EAA	5.M	Slight	Chisel	Galv	Plain	Box
1"	AY13EAA	5.M	Slight	Chisel	Galv	Plain	Box
5/8"	AX10EAA	5.M	Medium	Chisel	Galv	Plain	Box
3/4"	AX11EAA	5.M	Medium	Chisel	Galv	Plain	Box
1"	AX13EAA	5.M	Medium	Chisel	Galv	Plain	Box
1 1/4"	AX15EAA	5.M	Medium	Chisel	Galv	Plain	Box

Specifications

Item#	2D0101N
Mode of Operation	Sequential Actuation Trigger
Reg. Operating Pressure	70-120 psi (4.8 - 8.3 bar)
Air Consumption (60 cycles per min.)	3.2 scfm
Air Inlet	1/4" NPT
Tool Weight	2.75 lbs (1.25kg)
Height	10" (254 mm)
Length	13" (330 mm)
Width	3.4" (86 mm)
Fastener Capacity	110



Fastener Specifications

Gauge	18
Fastener Range:	
Brads	5/8" - 1 1/4" (16mm - 32mm)
Staples	1/2" - 1" (12mm - 25mm)
Finish	Galvanized
Collation	Glued strip

SENCO® 18 Ga. 1/4" Crown Medium Wire

Cabinets, casebacks, drawers, upholstery, soffits, underlayment, lattice & insulative sheathing

Length	Item Code	Carton Count	Point	Finish	Coating	Package
3/4"	L11BRB	5.M	Chisel	Bright	Sencote	Box
1"	L13BRBN	5.M	Chisel	Bright	Sencote	Box
1"	L13BRBP	5.M	Chisel	Bright	Sencote	Box
1/2"	L08BAB	10.M	Chisel	Galv	Sencote	Box
5/8"	L10BABN	5.M	Chisel	Galv	Sencote	Box
5/8"	L10HABN	5.M	Cross Cut Chisel	Galv	Sencote	Box
3/4"	L11BAB	5.M	Chisel	Galv	Sencote	Box
3/4"	L11HAB	5.M	Cross Cut Chisel	Galv	Sencote	Box
7/8"	L12BAB	5.M	Chisel	Galv	Sencote	Box
7/8"	L12BQB	5.M	Chisel	Class1 Galv	Sencote	Box
7/8"	L12LAA	5.M	Divergent	Galv	Sencote	Box
1"	L13BABN	5.M	Chisel	Galv	Sencote	Box
1"	L13HABN	5.M	Cross Cut Chisel	Galv	Sencote	Box
5/8"	A800629	1.2M	Chisel	Galv	Sencote	Clamshell
3/4"	A800759	.9M	Chisel	Galv	Sencote	Clamshell
1"	A801009	.9M	Chisel	Galv	Sencote	Clamshell
3/4"	L11BGA	5.M	Chisel	Stainless	Plain	Box
1"	A801007	.9M	Chisel	Stainless	Sencote	Clamshell



Performance. Power.
Productivity.™

FinishPro® 2n1

18 Ga. Finish Nailer and Stapler Features



***Choose the right actuation mode!**

Sequential Actuation (also known as restrictive trigger or trigger fire) operates in the following sequence - depress the safety element at the nose of tool against the work surface then pull the trigger. After each fastener is driven, release the trigger and lift the tool off the work surface before starting the sequence again. This trigger is recommended and acceptable for most applications.

Contact Actuation (also known as dual action, bounce or bottom fire) operates in the following sequence- pull the trigger first and keep the trigger pulled while moving the tool along the work surface with a bouncing motion, depressing the safety element at the nose of the tool against the work surface where the fastener is to be driven. This trigger is recommended for use by trained professionals only in high production or volume applications.

Always read the Operators Manual and Safety Instructions with all tool to ensure proper use and safety precautions. For additional information on trigger systems and how Senco will save you time, reduce costs and increase quality, call our toll-free Action Line: 800-543-4596, or visit our website at: www.senco.com