



Performance. Power.  
Productivity.™

# FinishPro® 42XP

## 15 Ga. 34° Finish Nailer

The FinishPro 42XP has established itself as the marquee tool for professional finish carpenters. The FinishPro 42XP has great durability and superior performance.



### Applications


Baseboards, cabinets, case goods, caskets, chair rails, decorative trim, door & window casing, sash & millwork, exterior trim, finish applications/trim, furniture and paneling.

### Features and Benefits

- Five year limited warranty
- Rugged internal engine design
- NeverLube® technology – no lubrication required
- Magnesium housing - lightweight and comfortable to use all day
- Thumb wheel adjustable depth-of-drive
- Comfort grip
- EZ-Clear™ latch – to clear jams fast
- 360° adjustable exhaust
- Two No-Mar pads with onboard storage to protect work materials
- Advanced belt hook – convenient storage

### Specifications

Item# . . . . . 4G0001N  
 Sequential Actuation  
 Reg. Operating Pressure . . . . . 70-120 psi (4.8 - 8.3 bar)  
 Air Consumption (60 cycles per min.) .. 3.87 scfm  
 Air Inlet . . . . . 1/4" NPT  
 Tool Weight . . . . . 4.7 lbs (2.1 kg)  
 Height . . . . . 11.25" (286 mm)  
 Length . . . . . 13" (330 mm)  
 Width . . . . . 3.5" (89 mm)  
 Fastener Capacity . . . . . 104



### Fastener Specifications

Gauge . . . . . 15  
 Fastener Range. . . . . 1 1/4" – 2 1/2" (32mm - 65mm)  
 Finish . . . . . Bright Basic, Galv. & Stainless  
 Collation . . . . . 34° angles mylar taped strip

### 15 Ga. 34° Angled Strip Finish Nails

Length	Item Code	Count	Point	Finish	Package
1/4	DA15EPBN	4.M	Chisel	Bright	Box
1/2	DA17EPBN	4.M	Chisel	Bright	Box
1 3/4	DA19EPBN	4.M	Chisel	Bright	Box
2	DA21EPBN	4.M	Chisel	Bright	Box
2 1/4	DA23EPBN	4.M	Chisel	Bright	Box
2 1/2	DA25EPB	3.M	Chisel	Bright	Box
1 1/2	A301500	0.7M	Chisel	Bright	Clamshell
1 3/4	A301750	0.7M	Chisel	Bright	Clamshell
2	A302000	0.7M	Chisel	Bright	Clamshell
2 1/2	A302500	0.7M	Chisel	Bright	Clamshell
1/4	DA15EABN	4.M	Chisel	Galv	Box
1/2	DA17EABN	4.M	Chisel	Galv	Box
1 3/4	DA19EABN	4.M	Chisel	Galv	Box
2	DA21EABN	4.M	Chisel	Galv	Box
2 1/2	DA25EAB	3.M	Chisel	Galv	Box
2	A302009	0.7M	Chisel	Galv	Clamshell
2 1/2	A302509	0.7M	Chisel	Galv	Clamshell
2	DA21EGBN	2.M	Chisel	Stainless	Box
2 1/2	DA25EGB	1.2M	Chisel	Stainless	Box
Reg. Galv Heat Treated*					
1/4	DA15AIA	4.M	Diamond	Hardened*	Box
1/2	DA17AIA	4.M	Diamond	Hardened*	Box
1 3/4	DA19AIA	4.M	Diamond	Hardened*	Box

\*Hardened 15 gauge for steel stud and trim application



Performance. Power.  
Productivity.™

# FinishPro® 42XP

## XtremePro™ FinishPro® 42XP Features

**360°**

**Adjustable Exhaust**

No tools required, quiet design

**Magnesium Mainbody**

Durable & ultra-light

**Internal Metal Cylinder**

Increased durability

**NeverLube® Design**

Oil-free operation

**Easy-Clear Guide Body**

To clear jams fast

**NeverLube® Design**

Oil-free operation

**No-Mar Pad**

Protects woodwork

**Over-molded Grip**

Reduces vibration and fatigue, increases productivity

**SENCO Exclusive NeverLube® Design**

Keeps the work surface free of oil

**Belt Hook**

Lets the tool go where you go

**5-Year Limited Warranty**

XP durability

**Tool-free Adjustable Depth-of-Drive**

Allows user to achieve precise fastener placement

**\*Choose the right actuation mode!**

**Sequential Actuation** (also known as restrictive trigger or trigger fire) operates in the following sequence - depress the safety element at the nose of tool against the work surface then pull the trigger. After each fastener is driven, release the trigger and lift the tool off the work surface before starting the sequence again. This trigger is recommended and acceptable for most applications.

**Contact Actuation** (also known as dual action, bounce or bottom fire) operates in the following sequence- pull the trigger first and keep the trigger pulled while moving the tool along the work surface with a bouncing motion, depressing the safety element at the nose of the tool against the work surface where the fastener is to be driven. This trigger is recommended for use by trained professionals only in high production or volume applications.

Always read the Operators Manual and Safety Instructions with all tool to ensure proper use and safety precautions. For additional information on trigger systems and how SENCO will save you time, reduce costs and increase quality, call our toll-free Action Line: 800-543-4596, or visit our website at: [www.senco.com](http://www.senco.com)