

.Perfect for construction, furniture and cabinets and picture frames It's one of the lightest 15 gauge tools around. Belt hook can be attached to either side of the tool for left or right handed users. An adjustable depth of drive countersinks nails to a consistent and controllable depth, and an adjustable exhaust helps provide greater comfort for the user.




## Specifications

Item#.....	620002N
Sequential Actuation	
Reg. Operating Pressure.....	70-120 psi (4.8 - 8.3 bar)
Air Consumption (60 cycles per min.) ...	2.16 scfm
Air Inlet.....	1/4" NPT
Tool Weight .....	3.6 lbs (1.6 kg)
Height.....	9.62" (244 mm)
Length .....	12" (305 mm)
Width .....	3.25" (82.5 mm)
Fastener Capacity .....	104

## Fastener Specifications

Gauge .....	15
Fastener Range .....	1" - 2"
Finish.....	Bright Basic, Galvanized, Stainless
Collation.....	34° angled taped strip



## 15 Ga. 34° Angled Strip Finish Nails

Length	Item Code	Count	Point	Finish	Package
<b>Bright Basic</b>					
1	DA13EPBN	4.M	Chisel	Bright	Box
1¼	DA15EPBN	4.M	Chisel	Bright	Box
1½	DA17EPBN	4.M	Chisel	Bright	Box
1¾	DA19EPBN	4.M	Chisel	Bright	Box
2	DA21EPBN	4.M	Chisel	Bright	Box
1½	A301500	0.7M	Chisel	Bright	Clamshell
1¾	A301750	0.7M	Chisel	Bright	Clamshell
2	A302000	0.7M	Chisel	Bright	Clamshell
<b>Galvanized</b>					
1¼	DA15EABN	4.M	Chisel	Galv	Box
1½	DA17EABN	4.M	Chisel	Galv	Box
1¾	DA19EABN	4.M	Chisel	Galv	Box
2	DA21EABN	4.M	Chisel	Galv	Box
2	A302009	0.7M	Chisel	Galv	Clamshell
<b>Stainless</b>					
2	DA21EGBN	2.M	Chisel	Stainless	Box
2½	DA25EGB	1.2M	Chisel	Stainless	Box
1¼	A301257	1.2M	Chisel	Stainless	Clamshell
1½	A301507	0.7M	Chisel	Stainless	Clamshell
1¾	A301757	0.7M	Chisel	Stainless	Clamshell
2	A302007	0.7M	Chisel	Stainless	Clamshell
<b>Reg. Galv Heat Treated*</b>					
1¼	DA15AIA	4.M	Diamond	Hardened*	Box
1½	DA17AIA	4.M	Diamond	Hardened*	Box
1¾	DA19AIA	4.M	Diamond	Hardened*	Box

\*Hardened 15 gauge for steel stud and trim application

## Applications

Baseboards, cabinets, case goods, caskets, chair rails, decorative trim, door & window casing, sash & millwork, exterior trim, finish applications/trim, furniture and paneling.

## Features and Benefits

- Lightweight – 3.6 lbs.
- NeverLube® design
- Belt hook – attached to either side
- Adjustable depth-of-drive
- EZ-Clear™ latch
- Adjustable exhaust for user comfort
- Ergonomically designed comfort grip handle
- No-Mar pad – to protect work surfaces
- Includes case
- 1-year limited warranty

Choose the right trigger system for your specific needs!

Sequential Actuation Trigger (also known as restrictive trigger or trigger fire) operates in the following sequence - depress the safety element at the nose of tool against the work surface then pull the trigger. After each fastener is driven, release the trigger and lift the tool off the work surface before starting the sequence again. This trigger is recommended and acceptable for most applications.

Contact Actuation Trigger (also known as dual action, bounce or bottom fire) operates in the following sequence- pull the trigger first and keep the trigger pulled while moving the tool along the work surface with a bouncing motion, depressing the safety element at the nose of the tool against the work surface where the fastener is to be driven. This trigger is recommended for use by trained professionals only in high production or volume applications.

Always read the Operators Manual and Safety Instructions with all tools to ensure proper use and safety precautions. For additional information on trigger systems and how Senco will save you time, reduce costs, and increase quality, call our toll-free Action Line: 800-543-4596 to find your nearest Authorized Senco Dealer, Distributor or visit our web site at: [www.senco.com](http://www.senco.com)